

V A L S P A R C O R P O R A T I O N
MATERIAL SAFETY DATA SHEET

PAGE 1
03-0004006

***** SECTION 1: PRODUCT IDENTIFICATION

MANUFACTURERS ADDRESS : 1101 THIRD STREET SOUTH, MINNEAPOLIS, MN 55415
MFG TELEPHONE NUMBER : (612) 332-7371
24 HR EMERGENCY PHONE NO : 1-888-345-5732
CHEMICAL NAME OR FAMILY : PAINT PRODUCT
FORMULA : NOT APPLICABLE
TRADE NAME : 03 4006 EXT SPAR VAR GLOSS
REVISION DATE : 07-31-00 DATE PRINTED : 09-08-00

***** SECTION 2: HAZARDOUS INGREDIENTS

NAME	WT %		
COMMON(NA):MINERAL SPIRITS	35-40%	TLV TWA	100.00 PPM
		TLV STEL	NOT ESTAB
CAS:64742-47-8 CHEMICAL: DISTILLATES (PETROLEUM),		OSHA PEL	100.00 PPM
HYDROTREATED LIGHT		CEILING	NOT ESTAB
		RECOMND	NOT ESTAB
*COMMON(2):ETHYLENE GLYCOL MONOPROPYL ETHER	< 5%	TLV TWA	NOT ESTAB
		TLV STEL	NOT ESTAB
CAS:2807-30-9 CHEMICAL: ETHANOL,2-PROPOXY-		OSHA PEL	NOT ESTAB
		CEILING	NOT ESTAB
		RECOMND	25.00 (01)
COMMON(NA):PROPRIETARY ADDITIVE		TLV TWA	NOT ESTAB
		TLV STEL	NOT ESTAB
CAS:TRADE SECRET		OSHA PEL	NOT ESTAB
		CEILING	NOT ESTAB
		RECOMND	NOT ESTAB
COMMON(NA):DIPENTENE	5-10%	TLV TWA	100.00 PPM
		TLV STEL	NOT ESTAB
CAS:138-86-3 CHEMICAL: CYCLOHEXENE,1-METHYL-4-(1		OSHA PEL	NOT ESTAB
-METHYLETHENYL)-		CEILING	NOT ESTAB
		RECOMND	NOT ESTAB

CHEMICALS NOTED WITH A (*) ARE REPORTABLE UNDER SECTION 313 OF SARA TITLE III

- (1) = PPM SKIN
(2) = GLYCOL ETHER, SEE SECTION 5.

ALL COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH U.S. TSCA CHEMICAL
SUBSTANCE INVENTORY REQUIREMENTS.

***** SECTION 3: PHYSICAL DATA

BOILING POINT: 301 DEG F. (149 DEG C.)
VAPOR PRESSURE MM HG AT 98 DEG F. (36 DEG C): 10.0
VAPOR DENSITY (AIR = 1.0): 5.1
SPECIFIC GRAVITY. 0.90
PERCENT VOLATILE BY VOLUME: 54.04

V A L S P A R C O R P O R A T I O N
MATERIAL SAFETY DATA SHEET

PAGE 2
03-0004006

***** SECTION 3: PHYSICAL DATA
EVAPORATION RATE (BUTYL ACETATE = 1): 1.0
SOLUBILITY IN WATER: NO
APPEARANCE/ODOR: NORMAL FOR A COATINGS PRODUCT.
PH : N.AV
COEFFICIENT OF WATER/OIL DISTRIBUTION: N.AV

****CONTINUED****

***** SECTION 4: FIRE AND EXPLOSION HAZARD

FLASH POINT TCC/PM DEG F : 105
FLASH POINT TCC/PM DEG C : 40
LOWER EXPLOSIVE LIMIT : 1.00
UPPER EXPLOSIVE LIMIT : 16.00
AUTO IGNITION - DEG F : N.AV DEG C : N.AV
SENSITIVITY TO IMPACT : NONE
SENSITIVITY TO STATIC DISCHARGE : N.AV

EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, FOAM, AND/OR WATER FOG.

SPECIAL FIRE FIGHTING PROCEDURES

FIRE FIGHTERS MUST WEAR SELF CONTAINED BREATHING APPARATUS OR AIR MASKS.
CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS:

CONTAINS OXIDIZING MATERIALS. CONTAMINATED RAGS, WIPES, SAWDUST, ETC.
MAY CATCH FIRE SPONTANEOUSLY. STORE WASTE UNDER WATER IN CLOSED METAL
CONTAINERS UNTIL DISPOSED OF IN COMPLIANCE WITH ALL APPLICABLE REGULATIONS.

***** SECTION 5: HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: NOT REQUIRED FOR MIXTURE.

EFFECTS OF OVEREXPOSURE:

IMMEDIATE EFFECTS (ACUTE):

EYE IRRITATION.

HARMFUL IF INHALED MAY AFFECT THE BRAIN, NERVOUS SYSTEM OR RES-
PIRATORY SYSTEM, CAUSING DIZZINESS, HEADACHE, NAUSEA OR RESPIRATORY
IRRITATION.

MAY BE HARMFUL IF ABSORBED THROUGH SKIN.

OVEREXPOSURE TO INGREDIENTS IN THIS PRODUCT MAY CAUSE NOSE AND
THROAT IRRITATION, EYE IRRITATION, SKIN IRRITATION, HARMFUL IF
SWALLOWED, KIDNEY DAMAGE, BLOOD DAMAGE, HARM IF INHALED.

DELAYED EFFECTS (CHRONIC):

NOTICE: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL
OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM
DAMAGE INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND
INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.
CONTAINS INGREDIENTS WHICH MAY CAUSE KIDNEY DAMAGE, BLOOD DAMAGE.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE - ANY
RESPIRATORY OR SKIN CONDITION.

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15
MINUTES AND GET MEDICAL ATTENTION.
SKIN CONTACT: WASH THOROUGHLY WITH SOAP AND WATER.
CLOTHING: REMOVE CONTAMINATED CLOTHING AND SHOES. WASH CLOTHING
BEFORE REUSE. THOROUGHLY CLEAN CONTAMINATED SHOES.
INHALATION: IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE

V A L S P A R C O R P O R A T I O N
M A T E R I A L S A F E T Y D A T A S H E E T

PAGE 3
03-0004006

***** SECTION 5: HEALTH HAZARD DATA *****CONTINUED*****

ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE
OXYGEN. GET MEDICAL ATTENTION IMMEDIATELY.
SWALLOWING: IF SWALLOWED, INDUCE VOMITING IMMEDIATELY AS DIRECTED BY
MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN
UNCONSCIOUS PERSON.

POSSIBLE ROUTES OF ENTRY: INHALATION, INGESTION, SKIN ABSORPTION.

***** SECTION 6: REACTIVITY DATA *****

THIS PRODUCT IS STABLE
CONDITIONS TO AVOID: NONE
INCOMPATIBILITY: NA

HAZARDOUS DECOMPOSITION PRODUCTS:
PHENOLICS CARBON DIOXIDE/MONOXIDE

HAZARDOUS POLYMERIZATION: NONE

***** SECTION 7: SPILL OR LEAK PROCEDURES *****

VENTILATE AREA. AVOID BREATHING OF VAPORS. USE SELF-CONTAINED
BREATHING APPARATUS OR AIRMASK FOR LARGE SPILLS IN A CONFINED AREA.
WIPE UP OR ABSORB ON SUITABLE MATERIAL AND SHOVEL UP.
AVOID CONTACT WITH EYES.

WASTE DISPOSAL METHOD:
DISPOSE IN CHEMICAL DISPOSAL AREA OR IN A MANNER THAT COMPLIES WITH LOCAL,
STATE, PROVINCIAL AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

***** SECTION 8: SPECIAL PROTECTION INFORMATION *****

RESPIRATORY PROTECTION:
UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ABOVE APPLICABLE
LIMITS, NO RESPIRATOR IS REQUIRED. IF RESPIRATOR IS REQUIRED, THE
APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) SHOULD BE
WORN DURING APPLICATION. FOLLOW RESPIRATOR MANUFACTURERS DIRECTIONS FOR
RESPIRATOR USE.

VENTILATION:
REQUIRED FOR SPRAYING OR IN A CONFINED AREA, VENTILATION EQUIPMENT SHOULD BE
EXPLOSION PROOF.

PROTECTIVE GLOVES: USUAL HAND PROTECTION FOR PAINT APPLICATION.
EYE PROTECTION: FOR SPRAY APPLICATION, USE CHEMICAL
GOGGLES AS A MINIMUM. OTHERWISE, USE SAFETY GLASSES
WITH SIDE SHIELDS AS A MINIMUM.
OTHER PROTECTIVE EQUIPMENT: USUAL CLOTHING FOR PAINTING OPERATIONS.

***** SECTION 9: SPECIAL PRECAUTIONS *****

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES KEEP CONTAINER
CLOSED WHEN NOT IN USE. DO NOT STORE ABOVE 120 DEG F. (49 DEG C.) BASED ON THE
PRODUCT FLASH POINT AND VAPOR PRESSURE, SUITABLE STORAGE SHOULD BE PROVIDED IN
ACCORDANCE WITH OSHA REGULATION 1910.106/ONTARIO OH&S REGULATION 851 SECTION 22.

V A L S P A R C O R P O R A T I O N
MATERIAL SAFETY DATA SHEET

PAGE 4
03-0004006

***** SECTION 9: SPECIAL PRECAUTIONS *****CONTINUED*****
EMPTY CONTAINERS MAY CONTAIN PRODUCT RESIDUE, INCLUDING FLAMMABLE OR EXPLOSIVE
VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEAR CONTAINER. ALL LABEL WARNINGS
MUST BE OBSERVED UNTIL THE CONTAINER HAS BEEN CLEANED OR RECONDITIONED.

ABBREVIATIONS USED:

OSHA-OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION;
IARC-INTERNATIONAL AGENCY FOR RESEARCH ON CANCER; LEL-LOWER EXPLOSIVE LIMITS;
UEL-UPPER EXPLOSIVE LIMITS; MG CU M-MILLIGRAMS PER METERS CUBED; MM-MILLIMETERS;
MPPCF-MILLIONS OF PARTICLES PER CUBIC FOOT; MSHA-MINE SAFETY AND HEALTH
ADMINISTRATION; NIOSH-NATIONAL INSTITUTE OF OCCUPATIONAL SAFETY AND HEALTH;
WEMIS-WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION SYSTEM; H-HOURS; HR-HOURS;
NA-NOT APPLICABLE; NOT EST-NOT ESTABLISHED; NTP-NATIONAL TOXICOLOGY PROGRAM;
PB-LEAD; PEL-PERMISSIBLE EXPOSURE LEVEL; PPM-PARTS PER MILLION;
TCC/PM-TAG CLOSED CUP/PENSKY-MARTEN; RECM-RECOMMENDED; TLV-THRESHOLD LIMIT VALUES.
N.AV-NOT AVAILABLE; N.AP-NOT APPLICABLE; C-CELSIUS; F-FAHRENHEIT

***** PREPARED BY SECTION

PREPARED BY: REGULATORY AFFAIRS DEPT.

MFG TELEPHONE NUMBER : (612) 332-7371

REVISION DATE : 07-31-00

DATE PRINTED : 09-08-00

***** DISCLAIMER SECTION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE.
THE VALSPAR CORPORATION MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO
RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA. THE VALSPAR
CORPORATION FURTHER ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY
DAMAGE TO VENDEES, USERS, OR THIRD PARTIES CAUSED BY THIS MATERIAL. SUCH
VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THIS MATERIAL.